4K Slim Bezel Interactive Touch Displays

55" | 65" | 75" | 86"



Interactive whiteboard solution for meeting rooms with integrated annotation and mirroring software

Modern Interactive Whiteboard


The stylish enclosure design really makes this touch screen stand out from the crowd. The bezels are so thin that the display area occupies more than 91% of the overall screen size. Designed with aluminium bezels and a moulded polymer rear, the screen is so lightweight it can even be mounted on a stud wall.



4K Display

The 4K Ultra HD display delivers incredible image quality with four times resolution higher than Full HD. Optimised for viewing distances both near and far the display allows your content to take center stage for all your visual communication.







Introducing MEETINGPAD: The Ultimate Collaboration Tool



Multi-Device Wireless Mirroring

Wirelessly project the displays of up to four smartphones, tablets, laptops, PCs or Macs. Using mobile devices you can mirror the display in both directions, and even take control of the touch screen. Mirroring via 5GHz allows for fast response, all without the need of external wires or transmitters.



Flexible Working Tools

Personalise your experience by changing the background colour of the display, as well as the colour and thickness of your drawing tools.



Smart Pen Stylus

There are two stylish interactive 'Smart Pens' included. These special styluses allows you to control the display wirelessly from anywhere in the room. You can change the pen tool colour, save annotated documents, navigate through a PowerPoint presentation or website and go back to the 'MeetingPad' home screen.


Easy File Sharing

Once your device is connected you can quickly and easily share documents, videos, images and audio files stored on your smartphone, tablet, laptop or PC directly to the touch screen. You can also share files from the touch screen to your device by scanning a QR code with your mobile or tablet.



Advanced Whiteboard Widgets

The screens feature advanced widgets for the whiteboard including a calendar, timer and a calculator. For drawing more technical diagrams there are rulers and compasses available. There are tools for temporarily hiding information from viewers with our spotlight and curtain widgets.



Up/ Down/Previous/Save

0

0

Ok/Select

Change Mode

Optional OPS Windows PC


For seamless integration onto existing networks an OPS PC can be installed into the rear of the display, allowing for ultimate flexibility to switch between Android and Windows effortlessly.



Touch Screen Monitor

As well as using the built in Android system these displays can also be used as a touch screen monitor by connecting a PC or laptop via HDMI and USB.

1. Touch USB 2. LAN 3. YPBPR In 4. AV In 5. AV Out 6. VGA Audio In 7. VGA 8. Earphones 9. SPDIF Earphone 10. HDM In x 2 11. RS-232 12. USB x2



Easy Access Ports and Controls

Quickly and conveniently connect your own laptop or devices to the screen using the front facing HDMI and Touch USB ports. There are also 3 USB ports and a USB-C port for easy access.



Freeze Frame Function

While your laptop is connected you can freeze the image on screen so that you can continue to work independently on your laptop.



20 Touch Points

Ideal for large group collaboration, up to twenty users can interact with the screen simultaneously when working on group projects.



Slim Bezel

The screens feature an extremely sleek and narrow bezel meaning that the enclosure to display area ratio is very low. The front is crafted from segmented aluminium to achieve ultimate precession while the polymer rear keeps the display super slim and lightweight.



Etched Glass

Improves tactility for smoother touch gestures, especially useful for multiple users. The anti-glare nano coating also diffuses external light improving optical clarity.





Integrated Speakers

The screens have two integrated super slim 10W speakers for presentations that include an audio element.



12W x 2 Integrated Speak

Key Features



Specification Table

Resolution Generator Status Display Area (mm) 1207.6x678.5 1428.2x803.2 1646x925.5 Aspect Ratio	1892.2x1064.2	
Aspect Ratio1.6.9Brightness (cd/m ²)500Colour Depth1.0.7G colorsColour Depth1.0.7G colorsColour Depth1.0.7G colorsColour Depth1.0.7G colorsContrast Ratio1.0.7G colorsLifespan4.000:1Touch Technology4.000:1Touch Points20 (10 Touch Points in MeetingPad Software)Glass Thickness4.000Response Time5.8Touch Point Accuracy $-11mm$ AudioSpeaker TypePowerSpeaker TypePowerVUSB x3, HDMI-In, Touch USB, USB Type-CRear PortsHDMI-In x2, USB(2.0) x1, USB(3.0) x1, Touch USB, USB Type-CPowerPower SupplyPower Supply $-2100 - 240V$ (50Hz60Hz)Power Supply1262x763x82.11486.1x901.3x88.91708.2x1026.5x89.1Package Size (WxHxD mm)1364x924x180TBCTBCVESA Holes (mm)400x400500x400600x400Net Weight (kg)26.7Quering Temperature-00°C to 50°CStorace Temperature-00°C to 50°C	1892.2x1064.2	
PanelFightness (cd/m²) 50 ColourColour $1.07 \le colors$ Colour Depth $1.07 \le colors$ Viewing Angle $1.07 \le colors$ Contrast Ratio $1.08 \times colors$ Iffespan $0.000 \mapsto 0.000 \mapsto 0.000$ Fouch Technology $0.000 \mapsto 0.000 \mapsto 0.000 \mapsto 0.000$ Galas Thickness $20 (10 Touch Points in MeetingPad Software)$ Galas Thickness $$		
PanelColour1.07G colorsColour Depth10 BitViewing Angle178°Contrast Ratio4,000.1Lifespan80,000 HoursTouch TechnologyInfraredTouch Points20 (10 Touch Points in MeetingPad Software)Glass Thickness4mmResponse Times8msTouch Point Accuracy±1mmAudioSpeaker Type2 x 20WVPortsFront PortsResponse TimeUSB x,3, HDMI-In, Tourch USB, USB Type-CRear PortsHDMI-In x2, USB(2.0) x1, USB(3.0) x1, Touch USB, VGA, VGA, VGA, VGA, VGA, VGA, VGA, VGA		
Colour DepthID BitViewing AngleID BitContrast RatioID BitLifespan80,000 HoursTouch TechnologyInfraredTouch Points20 (10 Touch Points in MeetingPad Software)Glass ThicknessImmersionResponse TimeSeaker TypeTouch Point SImmersionAudioSpeaker TypeAudioSpeaker TypePront PortsHDMI-In x2, USB(2.0) x1, USB (3.0) x1, Touch USB, VGA, VGA, VGA, VGA, VGA, VGA, VGA, VGA		
Viewing Angle 178° Contrast Ratio 4,000:1 Lifespan 80,000 Hours Touch Technology Infrared Touch Technology Infrared Glass Thickness 20 (10 Touch Points in MeetingPad Software) Glass Thickness 4mm Response Time 58ms Touch Point Accuracy 41mm Audio Speaker Type 2 x 20W Audio Speaker Type 2 x 20W Power Front Ports USB x3, HDMI-In, Touch USB, USB Type-C Rear Ports HDMI-In x2, USB(2.0) x1, USB(3.0) x1, Touch USB, VGA, VGA Audio In, AV In, AV Out, YPbPr Power Power Consumption 70W 130W 250W Mechanical Unit Size (WXHxD mm) 1262x763x82.1 1486.1x901.3x88.9 1708.2x1026.5x89.1 Mechanical VESA Holes (mm) 400x400 500x400 600x400 Mechanical Gross Weight (kg) 26.7 38 54 Gross Weight (kg) 35.25 46 69		
Contrast Ratio 4,000:1 Lifespan 80,000 Hours Touch Technology Infrared Touch Points 20 (10 Touch Points in MeetingPad Software) Glass Thickness 4mm Response Time s8ms Touch Point Accuracy ±1mm Audio Speaker Type 2 x 20W Audio Speaker Type 2 x 20W Power Front Ports USB x3, HDMI-In, Touch USB, USB Type-C Rear Ports HDMI-In x2, USB(2.0) x1, USB(3.0) x1, Touch USB, VGA Audio In, AV In, AV Out, YPbPr Power Supply AC110-240V (SHZ-60Hz) Power Consumption 70W 130W 250W Mechanical Unit Size (WXHXD mm) 1262x763x82.1 1486.1x901.3x88.9 1708.2x1026.5x89.1 Mechanical VESA Holes (mm) 400x400 500x400 600x400 Mechanical Gross Weight (kg) 26.7 38 54 Gross Weight (kg) 35.25 46 69 Operating Temperature -10°C to 50 °C 50rage Temperature -20°C to 60°C	178°	
Lifespan80,000 HoursBouch TechnologyInfraredInfraredCouch PointsGlass Thickness4mmResponse TimeCouch Point Accuracy41mmAudioSpeaker TypeCouch PointsAV PortsFont PortsAPOrtsPower SupplyAC110-240V (50Hz-60Hz)Power Consumption70W1364x924x180TBCTBCPokage Size (WxHxD mm)1364x924x180TBCTBCVESA Holes (mm)400x400500x400600x400AGI0x400		
Touch Technology Infrared Touch Points 20 (10 Touch Points in MeetingPad Software) Glass Thickness 4mm Response Time 58ms Touch Point Accuracy ±1mm Audio Speaker Type 2 x 20W AV Ports Front Ports USB x3, HDMI-In, Touch USB, USB Type-C Rear Ports HDMI-In x2, USB(2.0) x1, USB(3.0) x1, Touch USB, VGA, VGA Audio In, AV In, AV Out, YPbPr Power Power Supply AC110-240V (50Hz~60Hz) Power Consumption 70W 130W 250W Mechanical Unit Size (WxHxD mm) 1262x763x82.1 1486.1x901.3x88.9 1708.2x1026.5x89.1 Mechanical VESA Holes (mm) 400x400 500x400 600x400 Methanical VESA Holes (mm) 400x400 500x400 600x400 Net Weight (kg) 26.7 38 54 Gross Weight (kg) 35.25 46 69 Operating Temperature -10°C to 50 °C -20°C to 60°C -20°C to 60°C		
Touch Points Touch Points in MeetingPad Software) Glass Thickness 4mm Response Time 4mm Touch Point Accuracy 4mm Audio Speaker Type 2 x 20W Audio Speaker Type 2 x 20W Av Ports Front Ports USB x3, HDMI-In, Touch USB, USB Type-C Av Ports Power Supply HDMI-In x2, USB(2.0) x1, USB(3.0) x1, Touch USB, VGA, VGA Audio In, AV In, AV Out, YPbPr Power Power Supply AC110-240V (50Hz-60Hz) Power Consumption 70W 130W 250W Mechanical Unit Size (WxHxD mm) 1262x763x82.1 1486.1x901.3x88.9 1708.2x1026.5x89.1 Mechanical VESA Holes (mm) 400x400 500x400 600x400 Methanical Qperating Temperature -10°C to 50°C 50°G to 50°C		
Touch Glass Thickness 4mm Response Time <8ms		
Response Time \$8ms Touch Point Accuracy ±1mm Audio Speaker Type 2 x 20W Av Ports Front Ports 2 x 20W Av Ports Front Ports USB x3, HDMI-In, Tout USB, USB Type-C Rear Ports HDMI-In x2, USB(2.0) x1, USB(3.0) x1, Touch USB, VGA, VGA Audio In, AV Out, YPbPr Power Power Supply AC110-240V (50Hz-60Hz) Power Consumption 70W 130W 250W Poken Consumption 70W 1486.1x901.3x88.9 1708.2x1026.5x89.1 Mechanical VESA Holes (mm) 1364x924x180 TBC TBC Vesch Holes (mm) 400x400 500x400 600x400 Net Weight (kg) 26.7 38 54 Gross Weight (kg) 35.25 46 69 Operating Temperature -10°C to 50 °C -20°C to 60°C -20°C to 60°C	4mm	
Touch Point Accuracy ±1mm Audio Speaker Type 2 x 20W AV Ports Front Ports USB x3, HDMI-In, Touch USB, USB Type-C Rear Ports HDMI-In x2, USB(2.0) x1, USB(3.0) x1, Touch USB, VGA, VGA Audio In, AV In, AV Out, YPbPr Power Power Supply AC110-240V (50Hz-60Hz) Power Consumption 70W 130W 250W Mechanical Unit Size (WxHxD mm) 1262x763x82.1 1486.1x901.3x88.9 1708.2x1026.5x89.1 Package Size (WxHxD mm) 1364x924x180 TBC TBC VESA Holes (mm) 400x400 500x400 600x400 Net Weight (kg) 26.7 38 54 Gross Weight (kg) 35.25 46 69 Operating Temperature -10°C to 50 °C -20°C to 60°C		
Audio Speaker Type 2 x 20W AV Ports Front Ports USB x3, HDMI-In, Touch USB, USB Type-C Rear Ports HDMI-In x2, USB(2.0) x1, USB(3.0) x1, Touch USB, VGA, VGA Audio In, AV In, AV Out, YPbPr Power Power Supply AC110-240V (50Hz~60Hz) Power Consumption 70W 130W 250W Mechanical Unit Size (WxHxD mm) 1262x763x82.1 1486.1x901.3x88.9 1708.2x1026.5x89.1 Package Size (WxHxD mm) 1364x924x180 TBC TBC VESA Holes (mm) 400x400 500x400 600x400 Net Weight (kg) 26.7 38 54 Gross Weight (kg) 35.25 46 69 Operating Temperature -10°C to 50 °C -20°C to 60°C		
AV Ports Front Ports USB x3, HDMI-In, Touch USB, USB Type-C Rear Ports HDMI-In x2, USB(2.0) x1, USB(3.0) x1, Touch USB, VGA, VGA Audio In, AV In, AV Out, YPbPr Power Power Supply AC110-240V (50Hz~60Hz) Power Consumption 70W 130W 250W Unit Size (WxHxD mm) 1262x763x82.1 1486.1x901.3x88.9 1708.2x1026.5x89.1 Package Size (WxHxD mm) 1364x924x180 TBC TBC VESA Holes (mm) 400x400 500x400 600x400 Net Weight (kg) 26.7 38 54 Gross Weight (kg) 35.25 46 69 Operating Temperature -10°C to 50 °C -20°C to 60°C		
AV Ports Rear Ports HDMI-In x2, USB(2.0) x1, USB(3.0) x1, Touch USB, VGA, VGA Audio In, AV In, AV Out, YPbPr Power Power Supply AC110-240V (50Hz-60Hz) Power Consumption 70W 130W 250W Mechanical Unit Size (WxHxD mm) 1262x763x82.1 1486.1x901.3x88.9 1708.2x1026.5x89.1 Package Size (WxHxD mm) 1364x924x180 TBC TBC VESA Holes (mm) 400x400 500x400 600x400 Net Weight (kg) 26.7 38 54 Gross Weight (kg) 35.25 46 69 Operating Temperature -10°C to 50 °C -20°C to 60°C	2 x 20W	
Rear Ports HDMI-In x2, USB(2.0) x1, USB(3.0) x1, Touch USB, VGA, VGA Audio In, AV In, AV Out, YPPPr Power Supply Power Supply AC110-240V (50Hz~60Hz) Power Consumption 70W 130W 250W Unit Size (WxHxD mm) 1262x763x82.1 1486.1x901.3x88.9 1708.2x1026.5x89.1 Package Size (WxHxD mm) 1364x924x180 TBC TBC VESA Holes (mm) 400x400 500x400 600x400 Net Weight (kg) 26.7 38 54 Gross Weight (kg) 35.25 46 69 Operating Temperature -10°C to 50 °C -20°C to 60°C	USB x3, HDMI-In, Touch USB, USB Type-C HDMI-In x2, USB(2.0) x1, USB(3.0) x1, Touch USB, VGA, VGA Audio In, AV In, AV Out, YPbPr, RS232, RJ45, Earphone, SP	
Power Power Consumption 70W 130W 250W Unit Size (WxHxD mm) 1262x763x82.1 1486.1x901.3x88.9 1708.2x1026.5x89.1 Package Size (WxHxD mm) 1364x924x180 TBC TBC VESA Holes (mm) 400x400 500x400 600x400 Net Weight (kg) 26.7 38 54 Gross Weight (kg) 35.25 46 69 Operating Temperature -10°C to 50 °C -20°C to 60°C		
Power Consumption 70W 130W 250W Mechanical Unit Size (WxHxD mm) 1262x763x82.1 1486.1x901.3x88.9 1708.2x1026.5x89.1 Package Size (WxHxD mm) 1364x924x180 TBC TBC VESA Holes (mm) 400x400 500x400 600x400 Net Weight (kg) 26.7 38 54 Gross Weight (kg) 35.25 46 69 -10°C to 50 °C Storage Temperature -20°C to 60°C	AC110~240V (50Hz~60Hz)	
Package Size (WxHxD mm) 1364x924x180 TBC TBC VESA Holes (mm) 400x400 500x400 600x400 Net Weight (kg) 26.7 38 54 Gross Weight (kg) 35.25 46 69 Operating Temperature -10°C to 50 °C Storage Temperature -20°C to 60°C	350W	
VESA Holes (mm) 400x400 500x400 600x400 Net Weight (kg) 26.7 38 54 Gross Weight (kg) 35.25 46 69 Operating Temperature -10°C to 50 °C -20°C to 60°C	1954.4x1165.2x89	
Net Weight (kg) 26.7 38 54 Gross Weight (kg) 35.25 46 69 Operating Temperature -10°C to 50 °C Storage Temperature -20°C to 60°C	TBC	
Gross Weight (kg) 35.25 46 69 Operating Temperature -10°C to 50 °C Storage Temperature -20°C to 60°C	800x400	
Operating Temperature -10°C to 50 °C Storage Temperature -20°C to 60°C	66	
Storage Temperature -20°C to 60°C	83	
Environmental Storage Temperature -20°C to 60°C	-10°C to 50 °C	
Environmental	-20°C to 60°C 10% to 90% 10% to 90% Quad-core ARM Cortex-A55 4GB Mali-G52 MP2(2EE) 32GB USB 2.0 x2 10/100 Ethernet 2.4G/5G built-in Wifi	
Operating Humidity 10% to 90%		
Storage Humidity 10% to 90%		
CPU Quad-core ARM Cortex-A55		
RAM 4GB		
Graphic Engine Mali-G52 MP2(2EE)		
USB USB 2.0 x2		
LAN 10/100 Ethernet		
Wi-Fi 2.4G/5G built-in Wifi		
OS Android 11		
	User Manual (CD), Remote Control, Power Cable, 3m LAN Cable, 3m USB A Male to USB B Male Cable, 3m HDM Cable, Wi-Fi Aerial (x3), Pointer, Magnetic Whiteboard Pen (x 2), Smart Pen (x1), Batteries x2	
Optional Floor Stand/Trolley, Ceiling Mount, PushShare Dongle	Floor Stand/Trolley, Ceiling Mount, PushShare Dongle	
Warranty Period 5 Year Onsite Warranty (UK Mainland Only)		
Warranty Technical Support Lifetime		

Errors and omissions excepted



Why Choose Our Commercial Display Solutions?

